



HELPI SRL

Mobile 340 25 111 34 Fax 035 78.44.07 email : gambirasio@helpi.biz

SEMIAUTOMATIC PACKAGING MACHINE AM60





Semiautomatic shrink packaging film machine AM60:

AM60 packaging machine is a monobloc unit with a loading shovel, width 600 mm, to set and push the package to pack over the sealing bar, on the tunnel conveyor belt.

- Steel tunnel conveyor belt, Width 520 mm, speed adjustable by variator.
- Steel welding bar, Length 710 mm, max. stroke 380 mm; with pneumatic movement; powered welding bar height adjustment.
- Temperature and welding bar descent time are adjustable.
- Maximum sizes of flat film reel: Width 690 mm, external diameter 250 mm, film thickness for the best performance: from 20 to 120 micron.
- Powered superior and inferior unwinders.
- Standard stop product brush.
- Production from 4 to 15 packs per minute, depending on the pack dimensions.
- Shrink tunnel Width 600 x Height 420 mm.
- Insulated panels to reduce the tunnel passage.
- Compactor rollers on the oven outlet.
- Oven temperature adjustable up to 240°C.
- Installed electric power: 13,5 kW (three phases + earth).
- Standard work height: 930 mm.
- Weight: 600 Kg.





Layout AM60:

