



HELPI SRL

Mobile 333 9953049

Fax 035 78.44.07

email: gambirasio@helpi.biz

AUTOMATIC MONOBLOC PACKAGING MACHINE
Model: AM60ATR – Vacuum Pump S.p.A.





Automatic monobloc packaging machine AM60ATR:

Automatic packaging machine **AM60ATR** equipped with a loading system, width 600 mm, a loading conveyor to bring the product to be packaged over the sealing bar and subsequently on the tunnel conveyor belt.

- Pneumatically operated side pack composition zone.
- Side loading conveyor belt width 82 mm.
- Loading system stroke adjustable (max. useful: 370 mm).
- Motorized superior and inferior unwinders.
- Steel sealing bar: Length 710 mm, adjustable opening stroke up to 280 mm.
- Sealing bar temperature (max.230°C) and sealing time are adjustable.
- Film reel max. dimensions: width 700 mm, diameter 350 mm, film thickness 120 MICRON (for the best machine performance 40 - 100 MICRON).
- Production: up to 11 packs/hour, according to the product and the package sizes.
- Shrink tunnel: length 800 mm, tunnel's passage 500 x 300 mm.
Tunnel's conveyor speed adjustable from 2,2 to 11,3 mt/min.
Tunnel temperature adjustable up to 220°C.
- Installed electric power: 11 kW (three phases + earth – 400V).
- Air consumption 3 litres per cycle; operating pressure: 6BARs.
- Standard work height on adjustable feet: 930 mm.
- Weight: about 650 Kg.

